







Hose Couplings & Clamps

TECHNICAL DATA



| Hose Nipple in inch | Bore in mm | Weight in Kgs | CLAW COUPLINGS |
|---|---|-------------------------|---|
| 1/2 3/4 1 | 12.0 16.9 23.1 | 0.14 0.15 0.17 | With hose Nipple. Uniform size of claws permits safe, easy & quick mating of different sizes of claw couplings. |
| Female BSP Thread in inch | Bore in mm | Weight in Kgs | FEMALE THREAD COUPLING |
| 1/2 3/4 1 | 18.6 24.0 25.5 | 0.135 0.140 0.150 | Universal twist type coupling drop forged steel with female Thread end, capable of being mated with any size of coupling. |
| Male B.S.P Thread in inch | Bore in mm | Weight in Kgs | MALE THREAD COUPLING |
| 1/2 3/4 1 | 14.8 19.0 25.5 | 0.120 0.125 0.130 | Claw couplings with male threaded can be mated with any size of claw coupling. Short length and large bore |
| <p>Original packings are made of oil and temperature resistant rubber. One packing is required for each coupling.</p> | | | |
| Inner Dia in inch | For hose with Outer in mm | | HOSE CLAMPS |
| 1/2 3/4 1 | 22.5 - 25.5 29.5 - 32.5 37.0 - 40.0 | | Made of malleable cast iron shaped to provide a good Joint and tightened by a standard hexagon screw & nut. |
| Hose in inch | Bore in mm | Weight Kgs. | HOSE JOINTING NIPPLES |
| 1/2 3/4 1 | 12.0 16.9 23.1 | 0.03 0.08 0.11 | Made of steel having lock Border on both ends with a maximum of bore area. |

DESIGNED, DEVELOPED, SOLD & SERVICED BY :-



Micon Engineers

25, NETAJI SUBHAS ROAD, KOLKATA-700001
PHONE : 033-2230-9138/8378 • FAX : 033-22308378

email : miconeng@rediffmail.com