

Micon SOUND LEVEL METER



DESCRIPTION

- Large LCD display, easy to read Characteristic of "A" frequency weighting network are designed to meet IEC 61672 class 2.
- "Fast" time weighting characteristic mode
- Built-in adj. VR is available for easy calibration
- Condenser microphone for high accuracy & long-term stability
- Hold function to freeze the display value
- Warning indicator for over and under range
- LCD display for low power consumption & clear read-out even in bright ambient light condition
- Used the durable, long-lasting components, including a strong, light weight ABS-plastic housing case
- Small and light weight design allow one hand operation
- Low battery indicator
- Supplied with instruction manual

SPECIFICATION

- Display: 3½ Digit 18mm (0.7") LCD.
- Function: Db (A & C frequency weighting),
- Measurement Range : 3 ranges,
- 35 to 130 dB, 3 ranges, Data hold.
- Resolution: 0.1 dB.
- Accuracy: 23 + 5oC. Frequency: 31.5Hz ~ 8,000Hz.
- Time weighting (Fast, Slow), Max. Hold,
- AC and DC output



Micon Engineers

25 Netaji Subhas Road, Kolkata 700001
Ph:033-2230-9138/8378, Fax:033-2230-8378
Email: miconeng@rediffmail.com